

PROWAY - Professional Cellular Passive DAS



| C :C: .: | | |
|--------------------|---------------------------------|-----------------|
| Specifications: | | |
| Frequency Range | Band 12 | 698 - 746 MHz |
| | Band 13 | 746 - 787 MHz |
| | Band 5 | 824 - 894 MHz |
| | Band 25/2 | 1850 - 1995 MHz |
| | Band 4 | 1700 - 2155 MHz |
| Max Gain | 70dB | |
| Power Requirements | 110-240 V AC, 50-60 Hz, 20/30 W | |
| Connectors | N-Female | |
| Impedance | 50 Ohm | |
| Dimensions | 18.5 x 18.5 in x 3.25 in | |
| Warranty | 3 Year Equipment | |
| PROWAY Support | Lifetime | |
| | 866-912-3444 | |

Application:

Amplifies Weak Signal for All Carriers:

Verizon

AT&T

Sprint

T-Mobile

Alltel

US Cellular

And More...

Description

Powerful Signal specializes in Passive Cellular DAS systems designed with commercial grade amplifiers. PROWAY systems are custom designed to enhance in-building cellular coverage for all building types. Along with each professionally designed and installed system, we provide our exclusive Lifetime Support.



PowerfulSignal Solutions

Direct: 435-634-6800 • Toll Free: 866-912-3444 lee.stack@powerfulsignal.com