## Solid Connectivity is Our Obsession

## 698-2700MHz 3dBi Omni Antenna (Home, Office) Model: ANT090303/ANT090304

## **Features:**

- Optional built-in power divider, can be connected in series to eliminate dead zones and provide complete building coverage
- Sleek and compact design minimizes the space needed for the desktop antenna, and allows you to easily relocate the inside antennas suitable for home and office
- Compatible with all US carriers, including: AT&T, Verizon, T-Mobile, Sprint, U.S. Cellular, etc.
- Better incoming signal means less output power from your devices; extending battery life and significantly reducing exposure to electromagnetic radiation emitted by cellular devices
- SMA connector



	ANT090303	ANT090304
SMA connector number	2	1
Built-in power divider	Y	N

Floatuical Considirations				
Electrical Specifications				
Frequency Range	698-960 MHz	1710-2700 MHz		
Gain	3 dBi	5 dBi		
VSWR	≤2.0	≤1.5		
Polarization	Vertical			
Horizontal Beam width	360°			
Vertical Beam width	95°			
Input Impedance	50	50 Ω		
Max. Power	50 W			
Lightning Protection	DC Ground			
Mechanical Specifications				
Dimensions	203*75	203*75*75 mm		
Weight	0.3	0.35 kg		
Reflector Material	Aluminum			
Radome Material	ABS			
Operating Temperature	-40°C to +65 °C			