

Top Signal Dome Antenna with L-Bracket 698-2700MHz 3dB



PRODUCT No:
TS250373 Dome Antenna with L-Bracket

Features:

3 dBi
Indoor
Dome Antenna
L-Bracket
360 Degree Omni Directional

Specifications:

Frequency	698-2700 MHz
Gain	3 dBi
Horizontal Beam	360 degrees
Vertical Beam	80 degrees
VSWR	698-800 MHz: ≤ 2.0 800-2700 MHz ≤ 1.5
Input Impedance	50 ohm
Input Maximum Power	100 W
Lightning Protection	DC Ground
Antenna Connector	N-Female
Antenna Dimensions	190 x 90 mm
Antenna Weight	0.29 kg
Radiating Electrical Material	Alu
Reflector Material	Alu
Radome Material	ABS
Installation Pole size	0.62 x 2.0 in
Color	White

Description

This Top Signal 698-2700 MHz dome building antenna is designed to be mounted on the ceiling or wall in a room. It radiates a signal downward and in a 360 degree pattern. Works with all cell phone providers. This antenna is intended for inside use. It is not weatherproof.

This dome antenna is unique. It can be mounted on either the ceiling or a wall. It comes with mounting hardware for both scenarios. Works with ceiling thickness up to 1.25". Mounting hardware is included. Included is a short pigtail coax with N-Female and N-Male connector.

