

## Top Signal 4G Ultra-Thin Ceiling Mount Antenna 600–4000 MHz



**PRODUCT No: TS250376**  
**Ultra-Thin Ceiling Mount Antenna**

### Features:

3-4 dBi

Indoor

Ultra-Thin Antenna

N-female

360 Degree Omni Directional

### Specifications:

Frequency	600-4000 MHz
Gain	3 dBi (600-960 MHz)
Gain	4 dBi (1710-2700 MHz)
Gain	4 dBi (3300-4000 MHz)
Horizontal Beam	360 degrees
Vertical Beam	80 degrees
VSWR	<=1.8
Input Impedance	50 ohm
Input Maximum Power	100 W
Cable	10" RG58U, Blue
Lightning Protection	DC Ground
Antenna Connector	N-Female
Antenna Dimensions	190 x 8 mm
Antenna Weight	0.30 kg
Radome Material	ABS (UV stabilized)
Installation Pole size	0.62 x 2.0 in
Color	White

### Description

This Top Signal 600-4000 MHz ultra-flat ceiling antenna is designed to be mounted on the ceiling or wall in a room. It radiates a signal downward and in a 360 degree pattern. Works with all cell phone providers. This antenna is intended for inside use. It is not weatherproof.

This antenna is unique. Mounts to drywall ceiling or other drillable, horizontal surface no thicker than 1.5 inches (mounting nut included; ceiling access required for installation). Includes an N-female connector with 10-inch "pigtail" cable attachment.

