top signal

LTE Marine Antenna RFI Quick-Release 82-Inch Whip 8.5 dBi 698–2700 MHz

PRODUCT No: TS210902

LTE Omni 82 Inch Whip Antenna - RFI CDQ7100 series

| ip Antenna k Release 0 series | | Features: | |
|-------------------------------------|--|---|--|
| | | 4.5 to 8.5 dBi Gain | |
| | | Outdoor | |
| | | Omnidirectional | |
| | | FME Female Connector | r |
| | | Patented PCB based Meander™ collinear design | |
| | | Q-Fit® removable whi | p system for easy removal |
| | | Ideal for all 4G networks with true multi-band coverage | |
| | | | |
| | | Specifications: | |
| | | Frequency Range | 698-2700 MHz |
| | | Gain/VSWR | 8.5 dBi (698-960 MHz) / <2.5:1 |
| | | Gain/VSWR | 4.5 dBi (1710-2170 MHz) / <2.5:1 |
| | | Gain /VSWR | 5.5 dBi (2300-2700 MHz) / <2.5:1 |
| | | Vertical Beam | Horizontal Beam |
| | | 15° | 360° (698-960 MHz) |
| | | 15° | 360° (1710-2170 MHz) |
| | | 20 ° | 360° (2300-2700 MHz) |
| | | Input Impedance | 50 ohm |
| | | Input Power | 10 W |
| | | Length | 81.89 in (208.0 cm) |
| | | Radome Diameter | 0.614-0.885 in (1.56-2.25 cm) |
| | | Antenna Weight | 3.75 lbs (1.7 kg) |
| | | Radome Material | Fiberglass |
| | | Marine Mount | 6.7-in (17 cm) Stainless Steel Ferrule |
| | | RG58 Cable Color | White |
| | | Cable Length | 16.4 ft (5 m) |
| | | Antenna Connector | FME Female |

82-Inch Whip Antenna with Quick Release CDQ7100 series