

# Coax Cable Splitters, 75 Ohm

SKUs: 850034, 850035, 850036

## FEATURES

- 698-2700 MHz Band
- Cellular mobile communication
- Low insertion loss, low VSWR
- High isolation, low ripple
- Microstrip structure

⚠ **Warning:** Cancer and Reproductive Harm - [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)



850035 3-Way Splitter



850036 4-Way Splitter



850034 2-Way Splitter



## Specifications

### ELECTRICAL SPECIFICATIONS

Model	850034	850035	850036
Frequency (MHz)	698-2700		
Splitter Loss (dB)	3.0	4.5	6.0
Insertion Loss (dB)	0.4	0.5	0.6
VSWR	≤2.0:1	≤2.3:1	≤2.4:1
Isolation (dB)	≥20		
Power Capacity (W)	50		
Impedance (Ohm)	75		

### MECHANICAL SPECIFICATIONS

Model	850034	850035	850036
Connector	F-Female		
Dimensions (LxWxD in.)	3.6 x 3.5 x 0.8	4.0 x 4.7 x 0.8	4.0 x 4.7 x 0.8
Weight (oz)	7.04	10.88	11.04
Operating Temperature (°F)	-40-140		



2 Year Warranty